



INDEX FOR STEEL TUBING

ROUND SEAMLESS	36-41
ROUND WELDED	41-42
SQUARE (MECHANICAL)	43
RECTANGULAR (MECHANICAL)	43
SQUARE (STRUCTURAL)	44
RECTANGULAR (STRUCTURAL)	44

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



**C1015/1020 CARBON SEAMLESS
MECHANICAL TUBING
4130, 4140/4142 ALLOY SEAMLESS
MECHANICAL TUBING Annealed and Heat Treated**
Stock Lengths, 17' to 24'

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
1/8				23	.025	.325	.0935
24	.022	.081	.0242	22	.028	.319	.1038
22	.028	.069	.0290	21	.032	.311	.1172
21	.032	.061	.0318	20	.035	.305	.1271
20	.035	.055	.0336	19	.042	.291	.1494
18	.049	.027	.0398	18	.049	.277	.1706
5/32				17	.058	.259	.1964
24	.022	.112	.0315	16	.065	.245	.2152
22	.028	.100	.0384	15	.072	.231	.2330
21	.032	.092	.0425	14	.083	.209	.2582
3/16				13	.095	.185	.2841
26	.018	.152	.0327	12	.109	.157	.3097
24	.022	.143	.0390	11	.120	.135	.3268
22	.028	.131	.0478	10	.134	.107	.3449
21	.032	.123	.0533	13/32			
20	.035	.117	.0572	16	.065	.276	.2367
19	.042	.103	.0655	14	.083	.240	.2863
18	.049	.089	.0727	13	.095	.216	.3155
17	.058	.072	.0805	5/32	.156	.094	.4165
16	.065	.057	.0854	7/16			
7/32				26	.018	.401	.0807
24	.022	.175	.0463	24	.022	.393	.0977
22	.028	.166	.0571	23	.025	.388	.1103
20	.035	.148	.0687	22	.028	.381	.1226
18	.049	.120	.0888	21	.032	.373	.1388
16	.065	.088	.1069	20	.035	.367	.1506
1/4				19	.042	.353	.1776
26	.018	.214	.0446	18	.049	.339	.2036
24	.022	.206	.0536	17	.058	.321	.2354
23	.025	.200	.0601	16	.065	.307	.2589
22	.028	.194	.0664	14	.083	.271	.3147
21	.032	.187	.0745	13	.095	.247	.3480
20	.035	.180	.0804	12	.109	.219	.3830
19	.042	.166	.0933	11	.120	.197	.4075
18	.049	.152	.1052	10	.134	.169	.4351
17	.058	.134	.1189	5/32	.156	.125	.4698
16	.065	.120	.1284	15/32			
14	.083	.084	.1480	16	.065	.339	.2777
13	.095	.060	.1573	1/2			
12	.109	.032	.1641	26	.018	.464	.0927
9/32				24	.022	.456	.1123
22	.028	.225	.0757	23	.025	.450	.1268
20	.035	.211	.0920	22	.028	.444	.1411
18	.049	.183	.1217	21	.032	.436	.1599
5/16				20	.035	.430	.1738
24	.022	.268	.0684	19	.042	.416	.2054
23	.025	.263	.0769	18	.049	.402	.2360
22	.028	.256	.0852	17	.058	.384	.2738
21	.032	.249	.0960	16	.065	.370	.3020
20	.035	.242	.1039	15	.072	.356	.3291
19	.042	.228	.1216	14	.083	.334	.3696
18	.049	.214	.1382	13	.095	.310	.4109
17	.058	.196	.1580	12	.109	.282	.4552
16	.065	.182	.1722	11	.120	.260	.4870
14	.083	.146	.2039	10	.134	.232	.5238
13	.095	.122	.2212	5/32	.156	.187	.5731
12	.109	.094	.2375	3/16	.187	.125	.6264
11	.120	.072	.2473	17/32			
11/32				16	.065	.401	.3237
21	.032	.280	.1066	14	.083	.365	.3971
18	.049	.250	.1485	13	.095	.341	.4422
3/8				11	.120	.291	.5267
24	.022	.331	.0829				

DOM tubing available in diameters up to 10" and wall thickness up to .400".

**C1015/1020 CARBON SEAMLESS
MECHANICAL TUBING
4130, 4140/4142 ALLOY SEAMLESS
MECHANICAL TUBING Annealed and Heat Treated**
Stock Lengths, 17' to 24'

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
9/16				20	.035	.680	.2673
24	.022	.518	.1271	18	.049	.652	.3668
23	.025	.513	.1436	17	.058	.634	.4287
22	.028	.506	.1600	16	.065	.620	.4755
21	.032	.499	.1815	15	.072	.606	.5214
20	.035	.492	.1974	14	.083	.584	.5913
19	.042	.479	.2337	13	.095	.560	.6646
18	.049	.464	.2690	12	.109	.532	.7462
17	.058	.446	.3128	11	.120	.510	.8074
16	.065	.432	.3457	10	.134	.482	.8816
14	.083	.396	.4255	5/32	.156	.437	.9897
13	.095	.372	.4748	3/16	.187	.375	1.128
12	.109	.344	.5285	7/32	.219	.312	1.242
11	.120	.322	.5677	1/4	.250	.250	1.335
10	.134	.294	.6140	13/16			
5/32	.156	.250	.6781	24	.022	.768	.1859
3/16	.187	.187	.7529	22	.028	.756	.2347
5/8				20	.035	.742	.2908
24	.022	.581	.1417	18	.049	.714	.3998
23	.025	.575	.1602	17	.058	.697	.4677
22	.028	.569	.1785	16	.065	.682	.5193
21	.032	.561	.2027	14	.083	.646	.6471
20	.035	.555	.2205	13	.095	.622	.7285
19	.042	.541	.2615	12	.109	.594	.8195
18	.049	.527	.3014	11	.120	.572	.8881
17	.058	.509	.3512	10	.134	.544	.9717
16	.065	.495	.3888	5/32	.156	.500	1.095
15	.072	.481	.4252	3/16	.187	.437	1.255
14	.083	.459	.4805	7/32	.219	.375	1.389
13	.095	.435	.5377	1/4	.250	.312	1.503
12	.109	.407	.6007	27/32			
11	.120	.385	.6472	12	.109	.625	.8554
10	.134	.357	.7027	5/32	.156	.531	1.146
5/32	.156	.312	.7814	7/8			
3/16	.187	.250	.8774	24	.022	.831	.2004
7/32	.219	.187	.9496	22	.028	.819	.2533
1/4	.250	.125	1.001	21	.032	.811	.2881
21/32				20	.035	.805	.3140
13	.095	.466	.5692	18	.049	.777	.4323
3/16	.187	.282	.9367	17	.058	.759	.5061
11/16				16	.065	.745	.5623
24	.022	.643	.1565	15	.072	.731	.6175
23	.025	.638	.1770	14	.083	.709	.7021
22	.028	.631	.1974	13	.095	.685	.7914
21	.032	.624	.2242	12	.109	.657	.8917
20	.035	.617	.2441	11	.120	.635	.9676
18	.049	.589	.3344	10	.134	.607	1.060
17	.058	.571	.3902	5/32	.156	.562	1.198
16	.065	.557	.4325	3/16	.187	.500	1.379
14	.083	.521	.5363	7/32	.219	.437	1.534
13	.095	.497	.6017	1/4	.250	.375	1.669
12	.109	.469	.6740	5/32	.281	.313	1.783
11	.120	.447	.7279	3/16	.313	.250	1.879
10	.134	.419	.7928	15/16			
5/32	.156	.375	.8864	24	.022	.894	.2152
3/16	.187	.312	1.004	22	.028	.881	.2721
7/32	.219	.250	1.097	20	.035	.867	.3375
3/4				18	.049	.839	.4652
24	.022	.706	.1711	17	.058	.822	.5451
23	.025	.700	.1936	16	.065	.807	.6060
22	.028	.694	.2159	14	.083	.771	.7579
21	.032	.686	.2454				

Continued on following page.

DOM tubing available in diameters up to 10" and wall thickness up to .400".

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



**C1015/1020 CARBON SEAMLESS
MECHANICAL TUBING
4130, 4140/4142 ALLOY SEAMLESS
MECHANICAL TUBING Annealed and Heat Treated**
Stock Lengths, 17' to 24'

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
15/16 (Cont.)							
13	.095	.747	.8553	12	.109	.907	1.183
12	.109	.719	.9651	11	.120	.885	1.288
11	.120	.697	1.048	10	.134	.857	1.418
10	.134	.669	1.151	5/32	.156	.812	1.614
5/32	.156	.625	1.303	3/16	.187	.750	1.881
3/16	.187	.562	1.506	7/32	.219	.687	2.119
7/32	.219	.500	1.682	1/4	.250	.625	2.336
1/4	.250	.437	1.837	5/32	.281	.563	2.533
5/32	.281	.376	1.972	3/16	.313	.500	2.714
5/16	.313	.313	2.089	11/32	.344	.437	2.869
1							
24	.022	.956	.2298	3/8	.375	.375	3.004
22	.028	.944	.2907	1 3/16			
21	.032	.936	.3308	22	.028	1.131	.3469
20	.035	.930	.3607	21	.032	1.124	.3951
18	.049	.902	.4977	20	.035	1.117	.4310
17	.058	.884	.5835	18	.049	1.089	.5961
16	.065	.870	.6491	17	.058	1.071	.7000
15	.072	.856	.7136	16	.065	1.057	.7796
14	.083	.834	.8129	14	.083	1.021	.9795
13	.095	.810	.9182	13	.095	.997	1.109
12	.109	.782	1.037	12	.109	.970	1.256
11	.120	.760	1.128	11	.120	.947	1.369
10	.134	.732	1.239	10	.134	.920	1.508
5/32	.156	.687	1.406	5/32	.156	.875	1.719
3/16	.187	.625	1.630	3/16	.187	.812	2.008
7/32	.219	.562	1.827	7/32	.219	.750	2.266
1/4	.250	.500	2.003	1/4	.250	.687	2.504
5/32	.281	.437	2.158	5/16	.313	.562	2.925
5/16	.313	.375	2.297	1 1/4			
11/32	.344	.312	2.410	22	.028	1.194	.3654
3/8	.375	.250	2.503	20	.035	1.180	.4542
1 1/16							
24	.022	1.018	.2446	18	.049	1.152	.6285
22	.028	1.006	.3095	17	.058	1.134	.7384
20	.035	.992	.3843	16	.065	1.120	.8226
18	.049	.964	.5306	14	.083	1.084	1.034
17	.058	.946	.6225	13	.095	1.060	1.172
16	.065	.932	.6928	12	.109	1.032	1.328
14	.083	.896	.8687	11	.120	1.010	1.448
13	.095	.872	.9821	1/8	.125	1.000	1.502
12	.109	.844	1.111	10	.134	.982	1.597
11	.120	.822	1.209	5/32	.156	.937	1.823
10	.134	.795	1.330	3/16	.187	.875	2.132
5/32	.156	.750	1.511	7/32	.219	.812	2.411
3/16	.187	.687	1.757	1/4	.250	.750	2.670
7/32	.219	.625	1.974	5/32	.281	.687	2.908
1/4	.250	.562	2.171	3/16	.313	.625	3.132
5/32	.281	.500	2.347	11/32	.344	.562	3.329
5/16	.313	.437	2.507	3/8	.375	.500	3.504
3/8	.375	.313	2.755	7/16	.437	.375	3.798
1 1/8							
24	.022	1.081	.2592	22	.028	1.257	.3843
22	.028	1.069	.3280	21	.032	1.249	.4378
21	.032	1.061	.3735	20	.035	1.242	.4777
20	.035	1.055	.4074	18	.049	1.214	.6615
18	.049	1.027	.5631	17	.058	1.197	.7774
17	.058	1.009	.6609	16	.065	1.182	.8664
16	.065	.995	.7359	14	.083	1.146	1.090
14	.083	.959	.9237	13	.095	1.122	1.236
13	.095	.935	1.045	12	.109	1.094	1.402
				11	.120	1.072	1.529
				10	.134	1.044	1.687
				9	.148	1.017	1.841
				5/32	.156	1.000	1.928

**C1015/1020 CARBON SEAMLESS
MECHANICAL TUBING
4130, 4140/4142 ALLOY SEAMLESS
MECHANICAL TUBING Annealed and Heat Treated**
Stock Lengths, 17' to 24'

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
1 5/16 (Cont.)							
3/16	.187	.937	2.259	7/16	.438	.625	4.968
7/32	.219	.875	2.559	1/2	.500	.500	5.340
1/4	.250	.812	2.838	1 1/16			
5/32	.281	.750	3.097	22	.028	1.507	.4590
5/16	.313	.687	3.343	21	.032	1.499	.5232
3/8	.375	.562	3.757	20	.035	1.493	.5712
1 3/8							
24	.022	1.330	.3179	16	.065	1.432	1.040
22	.028	1.319	.4028	13	.095	1.372	1.489
20	.035	1.305	.5009	12	.109	1.345	1.693
18	.049	1.277	.6939	11	.120	1.322	1.849
17	.058	1.259	.8158	10	.134	1.295	2.045
16	.065	1.245	.9094	5/32	.156	1.250	2.344
14	.083	1.209	1.145	3/16	.187	1.187	2.761
13	.095	1.185	1.299	7/32	.219	1.124	3.144
12	.109	1.157	1.474	1/4	.250	1.062	3.506
11	.120	1.135	1.608	5/16	.313	.937	4.179
10	.134	1.107	1.776	3/8	.375	.812	4.758
5/32	.156	1.062	2.031	1 1/2			
11/64	.172	1.031	2.210	22	.028	1.569	.4776
3/16	.187	1.000	2.383	20	.035	1.555	.5943
7/32	.219	.937	2.704	18	.049	1.527	.8248
1/4	.250	.875	3.004	17	.058	1.509	.9707
5/32	.281	.813	3.283	16	.065	1.495	1.083
5/16	.313	.750	3.550	14	.083	1.459	1.367
3/8	.375	.625	4.005	13	.095	1.435	1.552
7/16	.438	.499	4.383	12	.109	1.407	1.765
1/2	.500	.375	4.673	11	.120	1.385	1.929
1 7/16							
21	.032	1.374	.4805	10	.134	1.357	2.134
20	.035	1.367	.5244	5/32	.156	1.312	2.447
18	.049	1.339	.7269	11/64	.172	1.281	2.669
16	.065	1.307	.9531	3/16	.187	1.250	2.885
14	.083	1.271	1.201	7/32	.219	1.187	3.289
13	.095	1.247	1.363	1/4	.250	1.125	3.671
11	.120	1.197	1.689	5/32	.281	1.063	4.033
10	.134	1.170	1.866	5/16	.313	1.000	4.386
5/32	.156	1.125	2.136	3/8	.375	.875	5.006
3/16	.187	1.062	2.510	7/16	.438	.749	5.553
7/32	.219	1.000	2.851	1/2	.500	.625	6.008
1/4	.250	.937	3.172	1 1/4			
1 1/2							
22	.028	1.444	.4402	16	.065	1.558	1.127
20	.035	1.430	.5476	11	.120	1.447	2.010
18	.049	1.402	.7593	5/32	.156	1.376	2.552
17	.058	1.384	.8932	3/16	.187	1.312	3.012
16	.065	1.370	.9962	7/32	.219	1.250	3.436
15	.072	1.356	1.098	1/4	.250	1.188	3.839
14	.083	1.334	1.256	5/32	.281	1.126	4.223
13	.095	1.310	1.426	1 3/4			
12	.109	1.282	1.619	20	.035	1.680	.6411
11	.120	1.260	1.769	19	.042	1.666	.7661
10	.134	1.232	1.955	18	.049	1.652	.8902
5/32	.156	1.187	2.239	17	.058	1.634	1.048
3/16	.187	1.125	2.634	16	.065	1.620	1.170
7/32	.219	1.062	2.996	14	.083	1.584	1.478
1/4	.250	1.000	3.338	13	.095	1.560	1.679
5/32	.281	.938	3.658	12	.109	1.532	1.910
5/16	.313	.875	3.968	11	.120	1.510	2.089
11/32	.344	.812	4.247	10	.134	1.482	2.313
3/8	.375	.750	4.506	5/32	.156	1.437	2.656
				8	.165	1.420	2.793
				7/16	.187	1.375	3.136
				1/2	.219	1.312	3.581
				3/4	.250	1.250	4.005

DOM tubing available in diameters up to 10" and wall thickness up to .400".

Continued on following page.

DOM tubing available in diameters up to 10" and wall thickness up to .400".

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



**C1015/1020 CARBON SEAMLESS
MECHANICAL TUBING
4130, 4140/4142 ALLOY SEAMLESS
MECHANICAL TUBING Annealed and Heat Treated**
Stock Lengths, 17' to 24'

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
1 3/4 (Cont.)				3/8	.375	1.250	6.508
1/2	.281	1.188	4.409	7/16	.438	1.125	7.307
5/16	.313	1.125	4.804	1/2	.500	1.000	8.010
3/8	.375	1.000	5.507	9/16	.563	.876	8.640
7/16	.438	.875	6.137	5/8	.625	.750	9.178
1/2	.500	.750	6.675	3/4	.750	.500	10.01
9/16	.563	.624	7.137				
5/8	.625	.500	7.509	2 1/16			
				16	.065	1.932	1.387
1 1 3/16				11	.120	1.822	2.490
16	.065	1.683	1.213	5/32	.156	1.750	3.177
14	.083	1.647	1.534	3/16	.187	1.689	3.765
11	.120	1.572	2.170	1/4	.250	1.562	4.841
9/8	.125	1.563	2.253	5/16	.313	1.437	5.850
5/32	.156	1.501	2.761				
3/16	.187	1.439	3.263	2 1/8			
7/32	.219	1.375	3.728	18	.049	2.027	1.086
1/4	.250	1.313	4.173	16	.065	1.995	1.430
				14	.083	1.959	1.810
1 7/8				13	.095	1.935	2.060
20	.035	1.805	.6878	12	.109	1.907	2.347
18	.049	1.777	.9556	11	.120	1.885	2.570
16	.065	1.745	1.257	5/32	.156	1.812	3.281
14	.083	1.709	1.589	3/16	.187	1.750	3.889
13	.095	1.685	1.806	7/32	.219	1.687	4.458
12	.109	1.657	2.056	1/4	.250	1.625	5.006
11	.120	1.635	2.249	5/32	.281	1.563	5.534
10	.134	1.607	2.492	3/16	.313	1.500	6.057
5/32	.156	1.562	2.864	3/8	.375	1.375	7.009
3/16	.187	1.500	3.387	7/16	.438	1.250	7.892
7/32	.219	1.437	3.873	1/2	.500	1.125	8.678
1/4	.250	1.375	4.339	9/16	.563	1.000	9.392
5/32	.281	1.313	4.784	5/8	.625	.875	10.01
3/16	.313	1.250	5.222				
3/8	.375	1.125	6.008	2 1/4			
13/32	.406	1.063	6.370	17/32	.524	1.125	11.39
7/16	.438	1.000	6.722				
1/2	.500	.875	7.343	2 3/16			
5/16	.563	.750	7.889	13	.095	1.997	2.124
				11	.120	1.948	2.650
1 1 1/16				3/16	.188	1.812	4.016
12	.109	1.720	2.129	1/4	.250	1.688	5.174
11	.120	1.698	2.330				
9/8	.125	1.688	2.420	2 1/2			
5/32	.156	1.626	2.969	18	.049	2.152	1.152
7/32	.219	1.499	4.021	16	.065	2.120	1.517
1/4	.250	1.437	4.507	14	.083	2.084	1.921
3/8	.375	1.188	6.260	13	.095	2.060	2.186
				12	.109	2.032	2.492
2				11	.120	2.010	2.730
20	.035	1.930	.7345	10	.134	1.982	3.028
18	.049	1.902	1.021	5/32	.156	1.937	3.489
16	.065	1.870	1.343	3/16	.187	1.875	4.140
14	.083	1.834	1.699	7/32	.219	1.812	4.750
13	.095	1.810	1.933	1/4	.250	1.750	5.340
12	.109	1.782	2.201	5/32	.281	1.688	5.909
11	.120	1.760	2.409	3/16	.313	1.625	6.475
9/8	.125	1.751	2.503	11/32	.344	1.562	7.002
10	.134	1.732	2.670	3/8	.375	1.500	7.509
5/32	.156	1.687	3.072	13/32	.406	1.438	7.996
3/16	.187	1.625	3.638	7/16	.438	1.375	8.476
7/32	.219	1.562	4.166	1/2	.500	1.250	9.345
1/4	.250	1.500	4.673	9/16	.563	1.124	10.14
5/32	.281	1.438	5.159	5/8	.625	1.000	10.85
3/16	.313	1.375	5.639	11/16	.688	.874	11.48
11/32	.344	1.312	6.084	3/4	.750	.750	12.02

DOM tubing available in diameters up to 10" and wall thickness up to .400"

*Also stocked to O.D. and I.D. dimensions.

**C1015/1020 CARBON SEAMLESS
MECHANICAL TUBING
4130, 4140/4142 ALLOY SEAMLESS
MECHANICAL TUBING Annealed and Heat Treated**
Stock Lengths, 17' to 24'

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
2 5/16				1/2	.500	1.625	11.35
11	.120	2.073	2.811	9/16	.563	1.501	12.40
3/16	.187	1.939	4.267	5/8	.625	1.375	13.35
1/4	.250	1.813	5.508	3/4	.750	1.125	15.02*
2 3/8				2 3/4			
18	.049	2.277	1.217	20	.035	2.680	1.015
16	.065	2.245	1.604	18	.049	2.652	1.413
14	.083	2.209	2.032	16	.065	2.620	1.864
13	.095	2.185	2.313	14	.083	2.584	2.364
11	.120	2.135	2.890	13	.095	2.560	2.694
5/32	.156	2.062	3.697	12	.109	2.530	3.074
3/16	.187	2.000	4.391	11	.120	2.510	3.371
7/32	.219	1.937	5.043	10	.134	2.482	3.744
1/4	.250	1.875	5.674	5/32	.156	2.437	4.322
5/32	.281	1.813	6.284	3/16	.187	2.375	5.144
3/16	.313	1.750	6.893	7/32	.219	2.312	5.920
3/8	.375	1.625	8.010	1/4	.250	2.250	6.675
7/16	.438	1.500	9.061	5/32	.281	2.188	7.410
1/2	.500	1.375	10.01	3/16	.313	2.125	8.147
9/16	.563	1.249	10.90	11/32	.344	2.062	8.839
5/8	.625	1.125	11.68	3/8	.375	2.000	9.512
3/4	.750	.875	13.02	7/16	.437	1.875	10.82
				1/2	.500	1.750	12.02
2 7/16				5/16	.563	1.625	13.15
1/4	.250	1.937	5.842	3/8	.625	1.500	14.18
5/16	.313	1.812	7.104	11/16	.688	1.374	15.15
				3/4	.750	1.250	16.02
2 1/2				7/8	.875	1.000	17.52
18	.049	2.402	1.283	1	1.000	.750	18.69
16	.065	2.370	1.690				
14	.083	2.334	2.143	2 25/32			
13	.095	2.310	2.440	15/32	.454	1.875	11.40
12	.109	2.282	2.783				
11	.120	2.260	3.050	2 13/16			
9/8	.125	2.250	3.171	1/4	.250	2.313	6.843
10	.134	2.232	3.386	1/2	.500	1.813	12.35
5/32	.156	2.187	3.905				
3/16	.187	2.125	4.642	2 7/8			
7/32	.219	2.062	5.335	16	.065	2.745	1.951
1/4	.250	2.000	6.008	13	.095	2.685	2.821
5/32	.281	1.937	6.659	11	.120	2.635	3.531
3/16	.313	1.875	7.311	9/32	.156	2.563	4.530
11/32	.344	1.812	7.921	3/16	.187	2.500	5.395
3/8	.375	1.750	8.511	7/32	.219	2.437	6.212
7/16	.438	1.625	9.646	1/4	.250	2.375	7.009
1/2	.500	1.500	10.68	5/32	.281	2.313	7.785
9/16	.563	1.375	11.65	3/16	.313	2.250	8.564
5/8	.625	1.250	12.52	7/8	.375	2.125	10.01
3/4	.750	1.000	14.02	7/16	.438	2.001	11.40
				1/2	.500	1.875	12.68
2 9/16				5/16	.563	1.751	13.90
3/16	.188	2.187	4.769	3/8	.625	1.625	15.02
1/4	.250	2.062	6.176	3/4	.750	1.375	17.02
2 5/8				2 1 1/16			
16	.065	2.495	1.777	1/4	.250	2.438	7.177
13	.095	2.435	2.567	1/2	.500	1.938	13.02
12	.109	2.407	2.929				
11	.120	2.385	3.210	3			
5/32	.156	2.312	4.114	16	.065	2.870	2.037
3/16	.187	2.250	4.893	14	.083	2.834	2.586
7/32	.219	2.187	5.627	13	.095	2.810	2.947
1/4	.250	2.125	6.341	12	.109	2.782	3.365
5/32	.281	2.063	7.035	11	.120	2.760	3.691
3/16	.313	2.000	7.729	10	.134	2.732	4.102
3/8	.375	1.875	9.011	5/32	.156	2.687	4.738
7/16	.438	1.751	10.23				

Continued on following page.

DOM tubing available in diameters up to 10" and wall thickness up to .400"

*Also stocked to O.D. and I.D. dimensions.

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



**C1015/1020 CARBON SEAMLESS
MECHANICAL TUBING
4130, 4140/4142 ALLOY SEAMLESS
MECHANICAL TUBING Annealed and Heat Treated**
Stock Lengths, 17' to 24'

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
3 (Cont.)				13	.095	3.185	3.328
3/16	.187	2.625	5.646	11	.120	3.135	4.172
1/2	.219	2.562	6.505	3/16	.187	3.000	6.399
3/4 *	.250	2.500	7.343	1/2	.219	2.937	7.382
5/32	.281	2.437	8.160	3/4	.250	2.875	8.344
5/16	.313	2.375	8.982	5/16	.313	2.750	10.24
11/32	.344	2.312	9.758	3/8	.375	2.625	12.02
3/8	.375	2.250	10.51	7/16	.438	2.501	13.74
7/16	.438	2.125	11.98	1/2	.500	2.375	15.35
1/2	.500	2.000	13.35	5/16	.563	2.249	16.91
9/16	.563	1.875	14.65	3/8	.625	2.125	18.36
5/8	.625	1.750	15.85	3/4	.750	1.875	21.03
11/16	.688	1.625	16.99	3 1/2			
3/4	.750	1.500	18.02	20	.035	3.430	1.295
7/8	.875	1.250	19.86	16	.065	3.370	2.385
1	1.000	1.000	21.36	14	.083	3.334	3.029
3 1/16				13	.095	3.310	3.455
3/4	.250	2.562	7.511	11	.120	3.260	4.332
5/16	.313	2.437	9.193	10	.134	3.232	4.817
3/8	.375	2.313	10.77	9/32	.156	3.188	5.571
3 5/8				3/16	.187	3.125	6.650
16	.065	2.995	2.124	1/2	.219	3.062	7.674
13	.095	2.935	3.074	3/4 *	.250	3.000	8.678
11	.120	2.885	3.851	5/32	.281	2.938	9.660
3/16	.187	2.750	5.897	5/16	.313	2.875	10.65
7/32	.219	2.687	6.797	11/32	.344	2.812	11.99
1/4	.250	2.625	7.676	3/8	.375	2.750	12.52
9/32	.281	2.563	8.535	7/16	.438	2.626	14.32
5/16	.313	2.500	9.400	1/2	.500	2.500	16.02
3/8	.375	2.375	11.01	5/16	.563	2.374	17.66
7/16	.438	2.250	12.57	11/32	.594	2.312	18.44
1/2	.500	2.125	14.02	3/8	.625	2.250	19.19
9/16	.563	2.000	15.40	3/4	.750	2.000	22.03
5/8	.625	1.875	16.69	1	.875	1.750	24.53
3/4	.750	1.625	19.02	1	1.000	1.500	26.70
7/8	.875	1.375	21.03	3 3/4			
3 3/4				16	.065	3.495	2.471
16	.065	3.120	2.211	11	.120	3.385	4.492
14	.083	3.084	2.807	3/16	.187	3.250	6.901
13	.095	3.060	3.201	1/4	.250	3.125	9.011
11	.120	3.010	4.010	9/32	.281	3.063	10.04
1/2	.125	3.000	4.172	5/16	.313	3.000	11.07
10	.134	2.982	4.459	3/8	.375	2.875	13.02
9/32	.156	2.937	5.155	7/16	.438	2.750	14.91
3/16	.187	2.875	6.148	1/2	.500	2.625	16.69
7/32	.219	2.812	7.089	5/16	.563	2.499	18.41
1/4 *	.250	2.750	8.010	3/8	.625	2.375	20.03
9/32	.281	2.688	8.910	3/4	.750	2.125	23.03
5/16	.313	2.625	9.818	3 1/4			
11/32	.344	2.562	10.68	16	.065	3.620	2.558
3/8	.375	2.500	11.51	13	.095	3.560	3.708
13/32	.406	2.438	12.33	11	.120	3.510	4.652
7/16	.438	2.376	13.15	10	.134	3.482	5.175
1/2	.500	2.250	14.69	9/32	.156	3.437	5.988
9/16	.563	2.126	16.16	3/16	.187	3.375	7.152
5/8	.625	2.000	17.52	7/32	.219	3.312	8.259
11/16	.688	1.874	18.83	1/4	.250	3.250	9.345
3/4	.750	1.750	20.03	9/32	.281	3.188	10.41
7/8	.875	1.500	22.19	5/16	.313	3.125	11.49
1	1.000	1.250	24.03	11/32	.344	3.062	12.51
3 7/8				3/8 *	.375	3.000	13.52
16	.065	3.245	2.298	7/16	.438	2.875	15.49

*Also stocked to O.D. and I.D. dimensions.

DOM tubing available in diameters up to 10" and wall thickness up to .400".

**C1015/1020 CARBON SEAMLESS
MECHANICAL TUBING
4130, 4140/4142 ALLOY SEAMLESS
MECHANICAL TUBING Annealed and Heat Treated**
Stock Lengths, 17' to 24'

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
3 3/4 (Cont.)				11/32	.344	3.562	14.35
1/2	.500	2.750	17.36	3/8 **	.375	3.500	15.52
9/16	.563	2.624	19.16	7/16	.438	3.375	17.83
5/8	.625	2.500	20.86	1/2	.500	3.250	20.03
11/16	.688	2.374	22.50	9/16	.563	3.124	22.17
3/4	.750	2.250	24.03	5/8	.625	3.000	24.20
7/8	.875	2.000	26.87	11/16	.688	2.874	26.17
1	1.000	1.750	29.37	3/4	.750	2.750	28.04
3 5/8				7/8	.875	2.500	31.54
14	.083	3.709	3.361	1	1.000	2.250	34.71
11	.120	3.635	4.812	1 1/8 *	1.125	2.000	37.55
3/16	.187	3.500	7.403	1 1/4 *	1.250	1.750	40.05
1/4	.250	3.375	9.679	4 3/8			
5/16	.313	3.249	11.91	11	.120	4.135	5.453
3/8	.375	3.125	14.02	3/16	.187	4.001	8.407
7/16	.438	3.000	16.08	1/4	.250	3.875	11.01
1/2	.500	2.875	18.02	5/16	.313	3.749	13.58
9/16	.563	2.750	19.91	3/8	.375	3.625	16.02
5/8	.625	2.625	21.69	7/16	.438	3.500	18.42
3/4	.750	2.375	25.03	1/2	.500	3.375	20.69
11/16	.813	2.249	26.59	5/8	.625	3.125	25.03
3 5/16				3/4	.750	2.875	29.04
11/16	.680	2.500	23.09	4 1/2			
4				13	.095	4.310	4.469
16	.065	3.870	2.732	12	.109	4.282	5.112
14	.083	3.834	3.472	11	.120	4.260	5.613
13	.095	3.810	3.962	10	.134	4.232	6.248
11	.120	3.760	4.973	9/32	.156	4.188	7.237
1/2	.125	3.750	5.173	3/16	.187	4.125	8.658
5/32	.156	3.687	6.404	7/32	.219	4.062	10.01
3/16	.187	3.625	7.654	1/4 **	.250	4.000	11.35
7/32	.219	3.562	8.843	9/32	.281	3.938	12.66
1/4 **	.250	3.500	10.01	5/16	.313	3.875	14.00
9/32	.281	3.438	11.16	3/8 **	.375	3.750	16.52
5/16	.313	3.375	12.33	7/16	.438	3.624	19.00
3/8	.375	3.250	14.52	1/2	.500	3.500	21.36
7/16	.438	3.126	16.66	5/8	.625	3.375	23.67
1/2	.500	3.000	18.69	3/4	.750	3.250	25.87
9/16	.563	2.875	20.67	11/16	.688	3.125	28.01
5/8	.625	2.750	22.53	3/4	.750	3.000	30.04
11/16	.688	2.624	24.34	7/8	.875	2.750	33.88
3/4	.750	2.500	26.03	1	1.000	2.500	37.38
7/8	.875	2.250	29.20	1 1/8	1.125	2.250	40.55
1	1.000	2.000	32.04	1 1/4 *	1.250	2.000	43.39
1 1/4 *	1.250	1.500	36.71	4 5/8			
4 1/4				3/16	.187	4.251	8.909
11	.120	3.885	5.133	1/4	.250	4.125	11.68
3/16	.187	3.751	7.905	5/16	.313	3.999	14.41
1/4	.250	3.625	10.35	11/32	.344	3.937	15.73
5/16	.313	3.500	12.74	3/8	.375	3.875	17.02
3/8	.375	3.375	15.02	7/16	.438	3.749	19.59
7/16	.438	3.249	17.25	1/2	.500	3.625	22.03
1/2	.500	3.125	19.36	5/8	.625	3.375	26.70
9/16	.563	2.999	21.42	3/4	.750	3.125	31.04
5/8	.625	2.875	23.36	4 3/4			
4 3/4				11	.120	4.510	5.934
13	.095	4.060	4.216	10	.134	4.482	6.606
11	.120	4.010	5.293	3/16	.187	4.376	9.160
10	.134	3.982	5.890	1/4	.250	4.250	12.02
9/32	.156	3.937	6.821	5/16	.313	4.125	14.83
3/16	.187	3.875	8.156				
1/4	.250	3.750	10.68				
5/16	.313	3.625	13.16				

*Also carried in Hot Rolled.

**Also stocked to O.D. and I.D. dimensions.

DOM tubing available in diameters up to 10" and wall thickness up to .400".

Continued on following page

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



Continued from preceding page.

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
4 3/4 (Cont.)				5/8	.625	4.250	32.54
3/8 †	.375	4.000	17.52	3/4	.750	4.000	38.05
7/16	.438	3.874	20.17	7/8	.875	3.750	43.22
1/2	.500	3.750	22.70	1	1.000	3.500	48.06
9/16	.563	3.624	25.18	1 1/4 *	1.250	3.000	56.74
5/8	.625	3.500	27.53	1 1/2 **	1.500	2.500	64.08
3/4	.750	3.250	32.04	5 5/8			
7/8	.875	3.000	36.21	5/16	.313	5.001	17.76
1	1.000	2.750	40.05	3/8	.375	4.875	21.03
4 7/8				1/2	.500	4.625	27.37
3/16	.188	4.499	9.411	5/8	.625	4.375	33.38
1/4	.250	4.375	12.35	5 3/4			
3/8	.375	4.125	18.02	11	.120	5.510	7.215
7/16	.438	3.999	20.76	3/16	.187	5.375	11.17
1/2	.500	3.875	23.36	1/4	.250	5.250	14.69
3/4	.750	3.375	33.04	5/16	.313	5.125	18.18
4 6 3/4				3/8 †	.375	5.000	21.53
35/64	.542	3.906	25.75	1/2	.500	4.750	28.04
5				5/8	.625	4.500	34.21
11	.120	4.760	6.254	3/4	.750	4.250	40.05
10	.134	4.732	6.964	7/8	.875	4.000	45.56
3/16	.187	4.625	9.662	1	1.000	3.750	50.73
1/4 †	.250	4.500	12.68	6			
5/16	.313	4.375	15.67	11	.120	5.760	7.536
3/8	.375	4.250	18.52	3/16	.187	5.625	11.67
7/16	.438	4.124	21.34	1/4 †	.250	5.500	15.35
1/2 †	.500	4.000	24.03	5/16	.313	5.374	19.01
9/16	.563	3.876	26.68	3/8	.375	5.250	22.53
5/8	.625	3.750	29.20	1/2 †	.500	5.000	29.37
3/4	.750	3.500	34.04	5/16	.562	4.876	32.69
7/8	.875	3.250	38.55	3/8	.625	4.750	35.88
1	1.000	3.000	42.72	1/4	.750	4.500	42.05
1 1/8	1.125	2.750	46.56	7/8	.875	4.250	47.89
1 1/4 *	1.250	2.500	50.06	1	1.000	4.000	53.40
1 3/8	1.375	2.250	53.23	1 1/4 **	1.250	3.500	63.41
1 1/2 **	1.500	2.000	56.07	1 1/2 **	1.500	3.000	72.09
5 5/8				6 1/4			
3/16	.313	4.501	16.09	11	.120	6.010	7.856
3/8	.375	4.375	19.02	3/16	.187	5.876	12.17
1/2	.500	4.125	24.70	1/4	.250	5.750	16.02
5/8	.625	3.875	30.04	5/16	.313	5.624	19.85
1	1.000	3.125	44.06	3/8 †	.375	5.500	23.53
5 1/4				1/2	.500	5.250	30.71
11	.120	5.010	6.575	5/8	.625	5.000	37.55
3/32	.156	4.938	8.487	3/4	.750	4.750	44.06
3/16	.187	4.875	10.16	7/8	.875	4.500	50.23
1/4	.250	4.750	13.35	1	1.000	4.250	56.07
5/16	.313	4.625	16.50	6 3/8			
3/8 †	.375	4.500	19.52	1 1/16	1.313	3.750	70.93
1/2	.500	4.250	25.37	6 2 5/8			
5/8	.625	4.000	30.87	3/4	.750	4.898	45.03
3/4	.750	3.750	36.05	6 1/2			
7/8	.875	3.500	40.88	10	.134	6.232	9.111
1	1.000	3.250	45.39	3/16	.188	6.124	12.67
1 1/4	1.250	2.750	53.40	1/4 †	.250	6.000	16.69
5 3/8				3/8	.375	5.750	24.53
3/16	.188	5.000	10.41	1/2 †	.500	5.500	32.04
5 1/2				5/16	.563	5.374	35.70
11	.120	5.260	6.895	3/8	.625	5.250	39.22
3/16	.187	5.125	10.67	1/4	.750	5.000	46.06
1/4 †	.250	5.000	14.02	3/8	.875	4.750	52.57
5/16	.313	4.875	17.34	1	1.000	4.500	58.74
3/8	.375	4.750	20.53	1 1/4 **	1.250	4.000	70.09
7/16	.438	4.624	23.68	1 1/2 **	1.500	3.500	80.10
1/2 †	.500	4.500	26.70				

*Also carried in Hot Rolled.
 **Carried in Hot Rolled only.
 †Also stocked to O.D. and I.D. dimensions.

DOM tubing available in diameters up to 10" and wall thickness up to .400".

C1015/1020 CARBON SEAMLESS MECHANICAL TUBING 4130, 4140/4142 ALLOY SEAMLESS MECHANICAL TUBING Annealed and Heat Treated Stock Lengths, 24' Random

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
6 5/8				8 1/4			
3/16	.187	6.251	12.92	1/4	.250	7.750	21.36
6 3/4				1/2	.500	7.250	41.39
1/4	.250	6.250	17.36	3/4	.750	6.750	60.08
3/8 †	.375	6.000	25.53	7/8	.875	6.500	68.92
1/2	.500	5.750	33.38	1	1.000	6.250	77.43
5/8	.625	5.500	40.88	8 1/2			
3/4	.750	5.250	48.06	1/4 †	.250	8.000	22.03
7/8	.875	5.000	54.90	3/8	.375	7.750	32.54
1	1.000	4.750	61.41	1/2 †	.500	7.500	42.72
7				5/8	.625	7.250	52.57
3/16	.187	6.625	13.68	3/4	.750	7.000	62.08
1/4 †	.250	6.500	18.02	1	1.000	6.500	80.10
3/8	.375	6.250	26.53	1 1/4 **	1.250	6.000	96.79
1/2 †	.500	6.000	34.71	1 1/2 **	1.500	5.500	112.1
5/8	.625	5.750	42.55	8 3/4			
3/4	.750	5.500	50.06	3/8	.375	8.000	33.54
1	1.000	5.000	64.08	1 1/32	.406	7.938	36.18
1 1/4 **	1.250	4.500	76.76	1/2	.500	7.750	44.06
1 3/8	1.375	4.250	82.60	3/4	.750	7.250	64.08
1 1/2 **	1.500	4.000	88.11	9			
7 1/4				1/4	.250	8.500	23.36
1/4	.250	6.750	18.69	3/8	.375	8.250	34.54
3/8 †	.375	6.500	27.53	1/2 †	.500	8.000	45.39
1/2	.500	6.250	36.05	3/4	.750	7.500	66.08
5/8	.625	6.000	44.22	1	1.000	7.000	85.44
3/4	.750	5.750	52.07	1 1/2 **	1.500	6.000	120.2
1	1.000	5.250	66.75	9 1/4			
7 1/2				1/2	.500	8.250	46.73
1/4 †	.250	7.000	19.36	9 1/2			
3/8	.375	6.750	28.54	1/4	.250	9.000	24.70
1/2 †	.500	6.500	37.38	5/16	.313	8.874	30.71
5/8	.625	6.250	45.89	3/8 †	.375	8.750	36.55
3/4	.750	6.000	54.07	1/2	.500	8.500	48.06
1	1.000	5.500	69.42	3/4 †	.750	8.000	70.09
1 1/4 **	1.250	5.000	83.44	1 †	1.000	7.500	90.78
1 1/2 **	1.500	4.500	96.12	1 1/8 **	1.125	7.250	100.6
7 5/8				1 1/4 **	1.250	7.000	110.1
3/16	.313	7.000	24.44	1 1/2 **	1.500	6.500	128.2
3/8	.375	6.875	29.04	9 3/4			
1/2	.500	6.625	38.05	1/2 †	.500	8.750	49.40
7 3/4				10			
1/4	.250	7.250	20.03	1/4 †	.250	9.500	26.03
3/16	.313	7.124	24.86	1/2 *	.500	9.000	50.73
3/8	.375	7.000	29.54	3/4 †	.750	8.500	74.09
1 1/32	.406	6.937	31.85	1 *	1.000	8.000	96.12
1/2	.500	6.750	38.72	1 1/8 **	1.125	7.750	106.6
5/8	.625	6.500	47.56	1 1/4 **	1.250	7.500	116.8
3/4	.750	6.250	56.07	1 1/2 **	1.500	7.000	136.2
1	1.000	5.750	72.09	10 1/2			
8				1/4 †	.250	10.00	27.37
1/4 †	.250	7.500	20.69	3/8 †	.375	9.750	40.55
3/16	.313	7.374	25.70	1/2 *	.500	9.500	53.40
3/8	.375	7.250	30.54	3/4 †	.750	9.000	78.10
1/2 †	.500	7.000	40.05	1 †	1.000	8.500	101.5
5/8	.625	6.750	49.23	1 1/2 **	1.500	7.500	144.2
3/4	.750	6.500	58.07	10 3/4			
1	1.000	6.000	74.76	3/8 †	.375	10.00	41.55
1 1/2 **	1.500	5.000	104.1	1/2 †	.500	9.730	54.74
				1 *	1.000	8.750	104.1

*Also carried in Hot Rolled.
 **Carried in Hot Rolled only.
 †Also stocked to O.D. and I.D. dimensions.

Continued on following page.

DOM tubing available in diameters up to 10" and wall thickness up to .400".

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



C1015/1020 CARBON SEAMLESS MECHANICAL TUBING 4130, 4140/4142 ALLOY SEAMLESS MECHANICAL TUBING Annealed and Heat Treated Stock Lengths, 24' Random

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
10 3/4 (Cont.)				3/4	.750	10.25	88.11
1 1/8**	1.125	8.500	115.6	1 *	1.000	9.750	114.8
1 1/4**	1.250	8.250	126.8	12			
1 1/2**	1.500	7.750	148.2	1/4 †	.250	11.50	31.37
11				3/8*	.375	11.25	46.56
1/2 †	.500	10.00	56.07	1/2*	.500	11.00	61.41
1 †	1.000	9.000	106.8	3/4 †	.750	10.50	90.11
11 3/4				1 *	1.000	10.00	117.5

*Also carried in Hot Rolled.
**Carried in Hot Rolled only.
†Also stocked to O.D. and I.D. dimensions.

SEAMLESS STEEL TUBING Cold Drawn to O.D. and I.D. Dimensions Low Carbon Stock Lengths, 24' Random

O.D.	I.D.	Nominal Wall	Estimated Wt. Lbs. Per Foot	O.D.	I.D.	Nominal Wall	Estimated Wt. Lbs. Per Foot
2	1 1/2	1/4	4.673	7	6 1/2	3/8	18.02
2 1/4	1 3/4	1/4	5.340	7 1/4	6 1/2	3/8	27.53
2 1/2	2	1/4	6.008	7 1/2	6 1/2	1/2	37.38
2 3/4	2 1/4	1/4	6.675	7 1/2	7	1/4	19.36
3	2 1/2	1/4	7.343	8	7	1/2	40.05
3 1/4	2 3/4	1/4	8.010	8	7 1/2	1/4	20.69
3 1/2	3	1/4	8.678	8 1/2	7 1/2	1/2	42.72
3 3/4	3	3/8	13.52	8 1/2	8	1/4	22.03
4	3 1/2	1/4	10.01	9	8	1/2	45.39
4 1/4	3 1/2	3/8	15.52	9 1/2	7 1/2	1	90.78
4 1/2	3 3/4	3/8	16.52	9 1/2	8	3/4	70.09
4 3/4	4	1/4	11.35	9 1/2	8 3/4	3/8	36.55
5	4	3/8	17.52	9 3/4	8 3/4	1/2	49.40
5	4	1/2	24.03	10	8 1/2	3/4	74.09
5	4 1/2	1/4	12.68	10	9 1/2	1/4	26.03
5 1/4	4 1/2	3/8	19.52	10 1/2	8 1/2	1	101.5
5 1/2	4 1/2	1/2	26.70	10 1/2	9	3/4	78.10
5 1/2	5	1/4	14.02	10 1/2	9 3/4	3/8	40.55
5 3/4	5	3/8	21.53	10 1/2	10	1/4	27.37
6	5	1/2	29.37	10 3/4	9 3/4	1/2	54.74
6	5 1/2	1/4	15.35	10 3/4	10	3/8	41.55
6 1/4	5 1/2	3/8	23.53	11	9	1	106.8
6 1/2	5 1/2	1/2	32.04	11	10	1/2	56.07
6 1/2	6	1/4	16.69	12	10 1/2	3/4	90.11
6 3/4	6	3/8	25.53	12	11 1/2	1/4	31.37
7	6	1/2	34.71				

BUTT WELDED STEEL TUBING Cold Drawn MT 1010

Stock Lengths, 5' to 24' Random
Continued from preceding page.

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
1 5/8				3/16	.187	1.625	3.638
5/32	.156	1.312	2.447	7/32	.219	1.562	4.166
3/16	.187	1.250	2.885	1/4	.250	1.500	4.673
7/32	.219	1.187	3.289	2 1/8			
1/4	.250	1.125	3.671	5/32	.156	1.812	3.281
5/32	.281	1.063	4.033	3/16	.187	1.750	3.889
3/16	.313	1.000	4.386	1/4	.250	1.625	5.006
1 3/4				2 1/4			
12	.109	1.532	1.910	3/16	.187	1.875	4.140
5/32	.156	1.437	2.656	1/4	.250	1.750	5.340
3/16	.187	1.375	3.136	1	.300	1.650	6.248
7/32	.219	1.312	3.581	2 3/8			
1/4	.250	1.250	4.005	7/32	.219	1.937	5.043
1 7/8				1/4	.250	1.875	5.674
5/32	.156	1.562	2.864	2 1/2			
3/16	.187	1.500	3.387	3/16	.187	2.125	4.642
1/4	.250	1.375	4.339	5/32	.219	2.062	5.335
2				1/4	.250	2.000	6.008
5/32	.156	1.687	3.072				

WELDED MECHANICAL STEEL TUBING Cold Rolled and Hot Rolled Bright Finish MT 1010

Stock Lengths, 3' to 24' Random

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
1/4				16	.065	.495	.3888
20	.035	.180	.0804	14	.083	.459	.4805
18	.049	.152	.1052	11/16			
16	.065	.120	.1284	20	.035	.617	.2441
5/16				18	.049	.589	.3344
22	.028	.257	.0852	16	.065	.557	.4325
20	.035	.243	.1039	3/4			
18	.049	.214	.1382	22	.028	.694	.2159
16	.065	.183	.1722	20	.035	.680	.2673
3/8				18	.049	.650	.3668
22	.028	.319	.1038	16	.065	.620	.4255
20	.035	.305	.1271	14	.083	.584	.5913
18	.049	.277	.1706	13	.095	.560	.6646
16	.065	.245	.2152	11	.120	.510	.8074
7/16				13/16			
20	.035	.367	.1506	22	.028	.756	.2347
18	.049	.339	.2036	20	.035	.742	.2908
17	.058	.321	.2354	18	.049	.714	.3998
16	.065	.307	.2589	16	.065	.682	.5193
1/2				7/8			
22	.028	.444	.1411	22	.028	.819	.2533
20	.035	.430	.1738	20	.035	.805	.3140
18	.049	.402	.2360	18	.049	.777	.4323
16	.065	.370	.3020	16	.065	.745	.5623
9/16				14	.083	.709	.7021
22	.028	.507	.1600	13	.095	.685	.7914
20	.035	.492	.1974	15/16			
18	.049	.464	.2690	20	.035	.867	.3375
16	.065	.432	.3457	18	.049	.839	.4652
5/8				16	.065	.807	.6060
24	.022	.581	.1417	14	.083	.771	.7579
22	.028	.569	.1785	1			
20	.035	.555	.2205	20	.035	.930	.3607
18	.049	.527	.3014	18	.049	.902	.4977

Continued on following page.

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



WELDED MECHANICAL STEEL TUBING

Cold Rolled and Hot Rolled
Bright Finish MT 1010

Stock Lengths, 3' to 24' Random
Continued from preceding page.

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
1 (Cont.)				18	.049	1.527	.8248
16	.065	.870	.6491	16	.065	1.495	1.083
14	.083	.834	.8129	14	.083	1.459	1.367
13	.095	.810	.9182	11	.120	1.385	1.929
12	.109	.782	1.037	10	.134	1.357	2.134
11	.120	.760	1.128	1 3/4			
1 1/16				20	.035	1.680	.6412
20	.035	.992	.3843	18	.049	1.652	.8902
18	.049	.964	.5306	16	.065	1.620	1.170
16	.065	.932	.6928	14	.083	1.584	1.478
14	.083	.896	.8687	13	.095	1.560	1.679
1 1/4				11	.120	1.510	2.089
22	.028	1.069	.3280	10	.134	1.482	2.313
20	.035	1.055	.4074	1 7/8			
18	.049	1.027	.5631	20	.035	1.805	.6878
17	.058	1.009	.6609	18	.049	1.777	.9556
16	.065	.995	.7359	16	.065	1.745	1.257
14	.083	.959	.9237	14	.083	1.709	1.589
13	.095	.935	1.045	13	.095	1.685	1.806
12	.109	.907	1.183	11	.120	1.635	2.249
11	.120	.885	1.288	2			
1 3/16				22	.028	1.944	.5897
20	.035	1.117	.4310	20	.035	1.930	.7345
18	.049	1.089	.5961	18	.049	1.902	1.021
16	.065	1.058	.7796	16	.065	1.870	1.343
14	.083	1.021	.9795	14	.083	1.834	1.699
1 1/4				13	.095	1.810	1.933
22	.028	1.194	.3654	12	.109	1.782	2.201
20	.035	1.180	.4542	11	.120	1.760	2.409
18	.049	1.152	.6285	10	.134	1.732	2.670
16	.065	1.120	.8225	2 1/8			
14	.083	1.084	1.034	20	.035	2.055	.7813
13	.095	1.060	1.172	18	.049	2.027	1.086
12	.109	1.032	1.328	16	.065	1.995	1.430
11	.120	1.010	1.448	14	.083	1.959	1.810
1 1/16				13	.095	1.935	2.060
20	.035	1.242	.4777	11	.120	1.885	2.570
18	.049	1.214	.6615	2 1/4			
16	.065	1.182	.8664	20	.035	2.180	.8280
14	.083	1.146	1.090	18	.049	2.152	1.152
1 3/8				16	.065	2.120	1.517
20	.035	1.305	.5004	14	.083	2.084	1.921
18	.049	1.277	.6939	13	.095	2.060	2.186
16	.065	1.245	.9094	12	.109	2.032	2.492
14	.083	1.209	1.145	11	.120	2.010	2.730
11	.120	1.135	1.608	10	.134	1.982	3.028
1 7/16				2 3/8			
18	.049	1.339	.7269	20	.035	2.305	.8747
16	.065	1.307	.9531	18	.049	2.277	1.217
1 1/2				16	.065	2.245	1.604
20	.035	1.430	.5476	14	.083	2.209	2.032
18	.049	1.402	.7593	13	.095	2.185	2.313
16	.065	1.370	.9962	2 1/2			
14	.083	1.334	1.256	20	.035	2.430	.9214
13	.095	1.310	1.426	18	.049	2.402	1.283
12	.109	1.282	1.619	16	.065	2.370	1.690
11	.120	1.260	1.769	14	.083	2.334	2.143
10	.134	1.232	1.955	13	.095	2.310	2.440
1 9/16				12	.109	2.282	2.783
20	.035	1.493	.5712	11	.120	2.260	3.050
1 5/8				10	.134	2.232	3.386
20	.035	1.555	.5944				

WELDED MECHANICAL STEEL TUBING

Cold Rolled and Hot Rolled
Bright Finish MT 1010

Stock Lengths, 3' to 24' Random

Continued from preceding page.

O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	O.D. and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
2 5/8				3 1/2			
20	.035	2.555	.9681	18	.049	3.402	1.806
18	.049	2.528	1.348	16	.065	3.370	2.385
16	.065	2.495	1.777	14	.083	3.334	3.029
14	.083	2.459	2.253	13	.095	3.310	3.455
13	.095	2.435	2.567	11	.120	3.260	4.332
11	.120	2.385	3.210	10	.134	3.232	4.817
7	.180	2.265	4.700	7	.180	3.140	6.382
2 3/4				3 3/4			
18	.049	2.652	1.414	16	.065	3.620	2.558
16	.065	2.620	1.864	14	.083	3.584	3.251
14	.083	2.584	2.364	13	.095	3.560	3.708
13	.095	2.560	2.694	11	.120	3.510	4.652
12	.109	2.530	3.074	7	.180	3.390	6.863
11	.120	2.510	3.371	4			
10	.134	2.482	3.744	18	.049	3.902	2.068
7	.180	2.390	4.941	16	.065	3.870	2.732
2 7/8				14	.083	3.834	3.472
18	.049	2.777	1.479	13	.095	3.810	3.962
16	.065	2.745	1.951	12	.109	3.782	4.530
11	.120	2.635	3.531	11	.120	3.760	4.973
7	.180	2.515	5.181	10	.134	3.732	5.533
3				7	.180	3.640	7.344
18	.049	2.902	1.544	4 1/4			
16	.065	2.870	2.038	16	.065	4.120	2.905
14	.083	2.834	2.586	13	.095	4.060	4.216
13	.095	2.810	2.947	11	.120	4.010	5.290
12	.109	2.782	3.365	4 1/2			
11	.120	2.760	3.691	16	.065	4.370	3.079
10	.134	2.732	4.102	14	.083	4.334	3.915
7	.180	2.640	5.421	13	.095	4.310	4.469
3 1/8				12	.109	4.282	5.112
18	.049	3.027	1.610	11	.120	4.260	5.613
16	.065	2.995	2.124	7	.180	4.140	8.305
14	.083	2.959	2.697	5			
13	.095	2.935	3.074	16	.065	4.870	3.426
11	.120	2.885	3.851	14	.083	4.834	4.359
3 1/4				12	.109	4.782	5.694
16	.065	3.120	2.211	11	.120	4.760	6.254
14	.083	3.084	2.807	7	.180	4.640	9.266
13	.095	3.060	3.201	5 1/2			
11	.120	3.010	4.011	11	.120	5.260	6.895
7	.180	2.890	5.902	10	.134	5.232	7.679
3 3/8				6			
16	.065	3.245	2.298	16	.065	5.870	4.120
11	.120	3.135	4.172	11	.120	5.760	7.536
				10	.134	5.732	8.395
				7	.180	5.640	11.19

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



SQUARE WELDED STEEL TUBING Mechanical Cold Rolled and Hot Rolled Bright Finish MT 1010

Square Tubing is an excellent structural shape in that it combines low cost with light weight and high strength. It can readily be welded, formed, punched and drilled, and the square shape adapts conveniently to simple fabrication.

Outside welding flash removed. Inside welding flash removed some sizes.
Stock Lengths, 3' to 24' Random

Size and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot	Size and Gauge	Wall Dec.	I.D.	Estimated Wt. Lbs. Per Foot
3/8 X 3/8				14**	.083	1.084	1.317
22	.028	.319	.132	11*	.120	1.010	1.844
20	.035	.305	.1618	1 1/2 X 1 1/2			
18	.049	.277	.2172	20	.035	1.430	.6973
16	.065	.245	.2740	18	.049	1.402	.9669
1/2 X 1/2				16**	.065	1.370	1.269
22	.028	.444	.1797	14*	.083	1.334	1.600
20	.035	.430	.2213	13	.095	1.310	1.815
18	.049	.402	.3005	11*	.120	1.260	2.252
16	.065	.370	.3845	1 3/4 X 1 3/4			
5/8 X 5/8				18	.049	1.652	1.134
20	.035	.555	.2808	16	.065	1.620	1.490
18	.049	.527	.3838	14*	.083	1.584	1.882
16	.065	.495	.4950	13*	.095	1.560	2.138
3/4 X 3/4				11*	.120	1.510	2.660
20	.035	.680	.3403	2 X 2			
18	.049	.652	.4671	18	.049	1.902	1.300
16	.065	.620	.6055	16	.065	1.870	1.711
14	.083	.594	.7529	14**	.083	1.834	2.164
11*	.120	.510	1.028	13*	.095	1.810	2.361
7/8 X 7/8				11*	.120	1.760	3.068
20	.035	.805	.3998	2 1/4 X 2 1/4			
18	.049	.777	.5504	16	.065	2.120	1.932
16	.065	.745	.7160	2 1/2 X 2 1/2			
14	.083	.709	.8940	16	.065	2.370	2.153
1 X 1				14*	.083	2.334	2.728
20	.035	.930	.4593	12*	.109	2.282	3.544
18	.049	.902	.6337	11*	.120	2.260	3.884
16**	.065	.870	.8265	7*	.180	2.140	5.679
14	.083	.834	1.034	3 X 3			
12	.109	.782	1.321	14*	.083	2.834	3.292
11*	.120	.760	1.436	12*	.109	2.782	4.285
1 1/8 X 1 1/8				11*	.120	2.760	4.700
20	.035	1.055	.5188	7*	.180	2.640	6.903
18	.049	1.027	.7170	3 1/2 X 3 1/2			
16	.065	.995	.9370	11*	.120	3.260	5.516
1 1/4 X 1 1/4				7*	.180	3.140	8.126
20	.035	1.180	.5783	4 X 4			
18	.049	1.152	.8003	11*	.120	3.760	6.332
16**	.065	1.120	1.048	7*	.180	3.640	9.351

*Carried in Hot Rolled only.

**Carried in Hot Rolled and Cold Rolled.

RECTANGULAR WELDED STEEL TUBING Mechanical, Hot Rolled, Bright Finish

Outside welding flash removed. Inside welding flash remains.
Stock Lengths, 5' to 24' Random

Size in Inches	Wall Thickness		Estimated Wt. Lbs. Per Foot	Size in Inches	Wall Thickness		Estimated Wt. Lbs. Per Foot
	Gauge	Decimal			Gauge	Decimal	
1 1/2 X 3/4	14	.083	1.176	4 X 2	11	.120	3.884
1 1/2 X 1	14	.083	1.317		7	.180	5.679
2 X 1	11	.120	1.844		4	.238	7.320
	16	.065	1.269		14	.083	3.292
2 X 1 1/4	14	.083	1.599	11	.120	4.700	
	11	.120	2.252	7	.180	6.900	
2 X 1 1/2	14	.083	1.740	5	.220	8.315	
2 1/2 X 1	11	.120	2.660	4	.238	8.940	
2 1/2 X 1 1/2	14	.083	1.882	4 X 3	7	.180	8.126
	14	.083	2.164	4	.238	9.814	
3 X 1	5	.220	5.325	5 X 2	7	.180	8.126
	14	.083	2.164	5 X 2 1/2	11	.120	5.922
3 X 1 1/2	14	.083	2.445	7	.180	8.737	
	12	.109	3.173	5 X 3	7	.180	9.351
3 X 2	11	.120	3.476	6 X 3	7	.180	10.57
	7	.180	5.067	4	.238	13.79	
3 X 2	14	.083	2.728	8 X 4	7	.180	14.24
	12	.109	3.544	4	.238	18.65	

WELDED MANDREL DRAWN TUBING

Close Tolerance I.D. Stock Lengths, 17' to 24' Random
Also see Seamless Mechanical Tubing

O.D.	Nominal Wall	Tolerance O.D.	Tolerance I.D.	Estimated Wt. Lbs. Per Foot
1 1/2	1/8	1.497-1.503	1.247-1.253	1.836
1 3/4	1/8	1.747-1.753	1.497-1.503	2.169
2	1/8	1.997-2.003	1.747-1.753	2.503
2 1/8	3/16	2.121-2.129	1.746-1.754	3.889
2 1/4	1/8	2.246-2.254	1.996-2.004	2.837
2 3/8	3/16	2.371-2.379	1.996-2.004	4.391
2 1/2	1/8	2.496-2.504	2.246-2.254	3.171
2 5/8	1/8	2.620-2.630	2.370-2.380	3.338
2 3/4	3/16	2.745-2.755	2.370-2.380	5.144
2 7/8	1/8	2.745-2.755	2.495-2.505	3.504
2 7/8	1/4	2.867-2.877	2.357-2.367	7.009
2 7/8	3/16	2.870-2.880	2.495-2.505	5.395
3	1/4	2.992-3.002	2.482-2.492	7.343
3	1/8	2.995-3.005	2.745-2.755	3.838
3 1/4	1/8	3.241-3.253	2.729-2.741	8.010
3 1/4	1/8	3.244-3.256	2.994-3.006	4.172
3 3/8	3/16	3.369-3.381	2.994-3.006	6.399
3 1/2	1/4	3.491-3.503	2.979-2.991	8.678
3 1/2	1/8	3.494-3.506	3.244-3.256	4.506
3 3/4	1/4	3.741-3.753	3.229-3.241	9.340
3 3/4	3/16	3.869-3.881	3.494-3.506	7.403
4	1/4	3.991-4.003	3.479-3.491	10.01
4 1/4	1/4	4.241-4.257	3.725-3.741	1.680
4 1/4	1/8	4.242-4.258	3.980-3.966	5.507
4 3/8	3/16	4.367-4.383	3.976-3.992	8.407
4 1/2	1/4	4.491-4.507	3.975-3.991	11.35
4 3/4	1/4	4.741-4.759	4.223-4.241	12.02
5	1/4	4.989-5.007	4.471-4.489	12.68
5 1/4	1/4	5.239-5.259	4.719-4.739	13.35
5 1/4	1/8	5.240-5.260	4.975-4.995	6.842
5 3/8	3/16	5.366-5.386	4.971-4.991	10.41
5 1/2	1/4	5.490-5.510	4.990-5.010	14.02
5 1/2	3/16	5.735-5.765	5.235-5.265	14.69
6	1/4	5.985-6.015	5.485-5.515	15.35
6 1/4	1/4	6.230-6.270	5.730-5.776	16.02
6 1/4	1/8	6.230-6.270	5.980-6.020	8.177
6 1/2	1/4	6.480-6.520	5.980-6.020	16.69
6 3/4	1/4	6.730-6.770	6.230-6.270	17.36
7	1/4	6.980-7.020	6.480-6.520	18.02

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



LIGHT WEIGHT BLACK PIPE

This is structural grade material for use in structural and ornamental applications. It is light wall, the walls being 20% lighter than the walls of standard pipe, thus effecting substantial savings. Butt welded, plain ends, not pressure tested.

Stock Length, 21' Random

Size in Inches	O.D. in Inches	Wall Thickness	Estimated Wt. Lbs. Per Foot	Size in Inches	O.D. in Inches	Wall Thickness	Estimated Wt. Lbs. Per Foot
1	1.315	.104	1.344	2	2.375	.121	2.920
1¼	1.660	.110	1.816	3	3.500	.188	6.630
1½	1.900	.114	2.176	4	4.500	.188	8.640

SQUARE HOLLOW STRUCTURAL TUBING ASTM A-36 A-500 A-501

Hollow Structural Tubing is a welded or seamless carbon steel tubing produced to ASTM Specifications and intended for applications such as structural columns, beams, racks, guard rails, etc. It provides high strength with less weight than many other structural shapes of equivalent size or weight. It is easy to fabricate and can readily be cut, bent, punched, flared, bolted and welded.

Nominal Size In.	Wall In.	Wt. Per Ft. Lb.	Nominal Size In.	Wall In.	Wt. Per Ft. Lb.
1 x 1"	.049	.63	5 x 5"	.120	.820
	.065	.83		.188	11.97
	.072	.91		.250	15.62
	.083	1.04		.313	19.08
	.095	1.17		.375	22.37
2 x 2"	.109	1.32	6 x 6"	.500	28.43
	.120	1.44		.188	14.53
	.065	1.67		.250	19.02
	.072	1.89		.313	23.34
	.083	2.16		.375	27.48
2-1/2 x 2-1/2"	.095	2.46	7 x 7"	.500	35.24
	.109	2.80		.188	17.08
	.120	3.07		.250	22.42
	.188	4.32		.313	27.59
	.250	5.41		.375	32.58
3 x 3"	.083	2.73	8 x 8"	.500	42.05
	.095	3.03		.188	19.63
	.109	3.54		.250	25.82
	.120	3.84		.313	31.84
	.188	5.59		.375	37.69
3-1/2 x 3-1/2"	.250	7.11	10 x 10"	.500	48.48
	.095	3.67		.625	59.32
	.109	4.29		.188	24.73
	.120	4.70		.250	32.63
	.188	6.87		.313	40.35
4 x 4"	.250	8.81	12 x 12"	.375	47.90
	.313	11.08		.500	62.46
	.375	11.74		.625	76.33
	.120	5.52		.250	39.43
	.188	8.30		.313	48.86
4 x 4"	.250	10.81	14 x 14"	.375	58.10
	.313	13.19		.500	76.07
	.375	15.94		.313	57.36
	.083	4.42		.375	68.31
	.095	4.97		.500	89.68
4 x 4"	.120	6.33	16 x 16"	.313	65.87
	.188	8.15		.375	78.52
	.250	12.21		.500	103.50
	.313	14.83			
	.375	17.27			
.500	21.63				

RECTANGULAR HOLLOW STRUCTURAL TUBING ASTM A-36 A-500 A-501

Hollow Structural Tubing is a welded or seamless carbon steel tubing produced to ASTM Specifications and intended for applications such as structural columns, beams, racks, guard rails, etc. It provides high strength with less weight than many other structural shapes of equivalent size or weight. It is easy to fabricate and can readily be cut, bent, punched, flared, bolted and welded.

Nominal Size In.	Wall In.	Wt. Per Ft. Lb.	Nominal Size In.	Wall In.	Wt. Per Ft. Lb.
2 x 1"	.049	.72	6 x 3"	.120	7.15
	.065	.94		.188	10.70
	.072	1.03		.250	13.91
	.083	1.18		.313	17.44
	.095	1.33		.375	20.57
2 x 1-1/2"	.109	1.51	6 x 4"	.188	11.97
	.120	1.64		.250	15.62
	.065	1.49		.313	19.08
	.072	1.64		.375	22.37
	.083	1.88		.500	28.43
2-1/2 x 1-1/2"	.095	2.14	7 x 5"	.188	14.53
	.109	2.43		.250	19.02
	.120	2.66		.313	23.34
	.065	1.67		.375	27.48
	.072	1.89		.500	35.24
3 x 2"	.083	2.16	8 x 4"	.188	14.53
	.095	2.46		.250	19.02
	.109	2.80		.313	23.34
	.120	3.07		.375	27.48
	.188	4.63		.500	35.24
4 x 3"	.250	5.71	8 x 6"	.188	17.08
	.065	1.99		.250	22.42
	.072	2.38		.313	27.59
	.083	2.73		.375	32.58
	.095	3.03		.500	42.05
5 x 2"	.109	3.54	9 x 7"	.188	19.63
	.120	3.84		.250	25.82
	.188	5.59		.313	32.58
	.250	7.11		.375	37.69
	.065	3.04		.500	48.85
5 x 3"	.083	3.86	10 x 2"	.188	14.65
	.120	5.52		.250	19.31
	.188	8.15		.188	17.08
	.250	10.51		.250	22.42
	.313	13.19		.313	27.59
5 x 3"	.313	13.19	10 x 3"	.375	32.58
	.065	3.04		.500	42.05
	.083	3.86		.188	19.63
	.120	5.52		.250	25.82
	.188	8.15		.313	31.84
5 x 3"	.250	10.51	10 x 4"	.375	37.69
	.313	13.19		.500	48.85
	.083	4.42		.625	59.32
	.120	6.33		.188	22.18
	.188	9.42		.250	29.23
5 x 3"	.250	12.21	12 x 4"	.313	36.10
	.313	14.83		.375	42.79
	.375	17.27		.500	55.66
	.500	21.63		.625	67.82
				.188	24.73
		.250	32.63		
		.313	40.35		
		.375	47.90		
		.500	62.46		
		.625	76.33		